



Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: JAX BDF Cling-Lube (Aerosol)

Product Code(s): JAX214

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation: Lubricant.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

JAX INC.

W134 N5373 CAMPBELL DRIVE

MENOMONEE FALLS, WI 53051 USA

Tel: +01-262-781-8850

Fax: +01-262-781-3906

E-mai: patty@jax.com

Web: www.jax.com

Further information obtainable from:

REACH Only Representative

B-Lands Consulting

WTC, 5 Place Robert Schuman, BP 1516

38025 Grenoble, FRANCE

Tel: +33 476 295 869

Fax: +33 476 295 870

Email: europa@reach-compliance.eu

Web: www.reachteam.eu

1.4 Emergency telephone number:

UK - National Poisons Emergency: +44 870 600 6266 (24h - health professionals only).

Ireland - National Poisons Information Centre: +353 1 8379964.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

H229 Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms: Not applicable.

Signal word: Warning

Hazard statements:

H229 Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)**Additional information:**

21.0 % by mass of the contents are flammable

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Hazardous components:**

| | | |
|---|--|---------|
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 | Propane ----- Flam. Gas 1, H220; Press. Gas C, H280 | 10-<25% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 | Butane ----- Flam. Gas 1, H220; Press. Gas C, H280 | 3-<5% |
| CAS: 148520-84-7 | Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts ----- Skin Sens. 1, H317 | 0.3-<1% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 | Zinc oxide ----- Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 0.3-<1% |
| CAS: 61789-86-4 EINECS: 263-093-9 | Sulfonic acids, petroleum, calcium salts. ----- Skin Sens. 1, H317 | 0.3-<1% |
| CAS: 156105-31-6 | Benzenesulfonic acid, mono- C20-24-alkyl derivs., calcium salts ----- Skin Sens. 1B, H317 | 0.3-<1% |
| CAS: 80939-62-4 EINECS: 279-632-6 | Amines, C11-14-branched alkyl, monohexyl and dihexyl phosphates ----- Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | 0.3-<1% |

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation:** Move patient to fresh air, if symptoms persist consult a doctor.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Remove contact lenses, if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call for a doctor immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in a cool, dry place in tightly closed receptacles.
Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from oxidising agents.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

106-97-8 Butane

| | |
|---------------------|---|
| WEL (Great Britain) | Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene) |
|---------------------|---|

Additional information: The lists valid during the making were used as basis.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Eye protection:

Safety glasses with side-shields (EN 166).

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form: Aerosol.
Colour: Light straw.

Odour: Nearly odourless.

Odour threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: Not determined.

Boiling point/Boiling range: Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.

Flammability (solid, gaseous): Not applicable.

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.
Upper: Not determined.

Oxidising properties: Not determined.

Vapour pressure: Not determined.

Density: Not determined.

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not applicable.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)

Solubility in / Miscibility with water: Not determined.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:
Dynamic: Not determined.
Kinematic: Not determined.

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No data available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:
 No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Keep away from heat and direct sunlight.

10.5 Incompatible materials Avoid strong oxidants, strong alkalis and strong acids.

10.6 Hazardous decomposition products Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values:

106-97-8 Butane

| | | |
|------------|---------|----------------|
| Inhalative | LC50/4h | 658 mg/L (rat) |
|------------|---------|----------------|

1314-13-2 Zinc oxide

| | | |
|------|------|--------------------|
| Oral | LD50 | > 5000 mg/kg (rat) |
|------|------|--------------------|

61789-86-4 Sulfonic acids, petroleum, calcium salts.

| | | |
|------|------|------------------------------|
| Oral | LD50 | >5000 mg/kg (rat) (OECD 401) |
|------|------|------------------------------|

Additional Information: *Contains <3% DMSO extract as measured by IP 346.

Primary irritant effect:

on the skin: No irritant effect known.

on the eye: No irritating effect known.

Sensitisation: No sensitising effects known.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

1314-13-2 Zinc oxide

| | |
|----------|--------------------------|
| LC50/96h | 1.1 mg/L (Rainbow Trout) |
|----------|--------------------------|

61789-86-4 Sulfonic acids, petroleum, calcium salts.

| | |
|----------|-------------------------------|
| LC50/96h | >10000 mg/L (Fish) (OECD 203) |
|----------|-------------------------------|

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)**Ecotoxicological effects:****Remark:** Harmful to fish**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation:** Do not allow product to reach sewage system.**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN Number**

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, non-flammable

14.3 Transport hazard class(es)

ADR



Class

2 5A Gases.

Label

2.2

IMDG, IATA



Class

2.2

Label

2.2

14.4 Packing group

ADR, IMDG, IATA

Not applicable.

14.5 Environmental hazards**Marine pollutant:**

No

14.6 Special precautions for user

Warning: Gases.

Danger code (Kemler):

-

EMS Number:

F-D,S-U

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.06.2016

Version number 1

Revision: 30.06.2016

Trade name: JAX BDF Cling-Lube (Aerosol)**Transport/Additional information:****ADR****Exempted quantities (EQ)**

Code: E0

Not permitted as Exempted Quantity

Tunnel restriction code:

E

IMDG**Limited quantities (LQ)**

1L

Exempted quantities (EQ)

Code: E0

Not permitted as Exempted Quantity

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

: Flammable aerosols, Hazard Category 3

Press. Gas C: Gases under pressure: Compressed gas

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3