



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: JAX Trolley-Glide FG-3H (Aerosol)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation: Lubricant (release agent).

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

JAX INC.
 W134 N5373 CAMPBELL DRIVE
 MENOMONEE FALLS, WI 53051 USA
 Tel: +01-262-781-8850
 Fax: +01-262-781-3906

Further information obtainable from:

B-Lands Consulting
 WTC, 5 Place Robert Schuman, BP 1516
 38025 Grenoble, FRANCE
 Tel: +33 476 295 869
 Fax: +33 476 295 870
 services@reachteam.eu
 www.reachteam.eu

1.4 Emergency telephone number

UK - National Poisons Emergency: +44 870 600 6266 (24h - health professionals only).
 Ireland - National Poisons Information Centre: +353 1 8379964.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



GHS02

Signal word: Danger

Hazard statements:

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Buildup of explosive mixtures possible without sufficient ventilation.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

Trade name: JAX Trolley-Glide FG-3H (Aerosol)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Hazardous components:**

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	Propane	Flam. Gas 1, H220; Press. Gas, H280	10-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000	Butane	Flam. Gas 1, H220; Press. Gas, H280	10-20%

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation:** Supply fresh air. Consult doctor if symptoms persist.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Remove contact lenses, if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call for a doctor immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.**For safety reasons unsuitable extinguishing agents:** Water with full jet.**5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

5.3 Advice for firefighters**Protective equipment:** No special measures required.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

Trade name: JAX Trolley-Glide FG-3H (Aerosol)**6.3 Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Keep away from heat and direct sunlight.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

Store in a cool, dry place in tightly closed receptacles.

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility: Store away from oxidizing agents.**7.3 Specific end use(s):** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****106-97-8 Butane**

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use respirators and components tested and approved under appropriate standards such as CEN (Central European Norms).

Protection of hands:

Protective gloves

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Eye protection:

Tightly sealed goggles (EN 166).

Body protection: Protective work clothing.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

Trade name: JAX Trolley-Glide FG-3H (Aerosol)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Compressed liquefied gas.
Colour: Amber.

Odour: Light

Odour threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: Not determined.

Boiling point/Boiling range: Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.

Flammability (solid, gaseous): Not determined.

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.

Upper: Not determined.

Oxidizing properties Not determined.

Vapour pressure: Not determined.

Density at 20°C: 0.88 g/cm³ (concentrate)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not applicable.

Solubility in / Miscibility with water: Not determined.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No data available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Keep away from heat and direct sunlight.

10.5 Incompatible materials No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

Trade name: JAX Trolley-Glide FG-3H (Aerosol)**10.6 Hazardous decomposition products**

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****LD/LC50 values:****106-97-8 Butane**

Inhalative	LC50/4h	658 mg/L (Rat)
------------	---------	----------------

Primary irritant effect:**on the skin:** No irritant effect.**on the eye:** No irritating effect.**Sensitization:** No sensitizing effects known.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation:** Do not allow product to reach sewage system.**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN Number**

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR

**Class**

2 5F Gases.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2017

Revision: 02.03.2017

Trade name: JAX Trolley-Glide FG-3H (Aerosol)**Label** 2.1**IMDG, IATA****Class** 2.1**Label** 2.1**14.4 Packing group****ADR, IMDG, IATA** Not applicable.**14.5 Environmental hazards****Marine pollutant:** No**14.6 Special precautions for user**

Warning: Gases.

Danger code (Kemler): -**EMS Number:** F-D,S-U**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

Transport/Additional information:**ADR****Tunnel restriction code:** D**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent